



Cutting Capacity Metal Sheet 4mm Compact and lightweight.

Easy recovery by the restart button in case of unexpected stop.



Noise reducer

Accessories

Blade: 32-tooth thick blade ASB-32H···1pc. 24-tooth thick blade ASB-24H···1pc.

Cutting Capacity Metal Sheet 1.6mm Compact and lightweight.



Accessories Blade : 32-tooth standard blade ASB-32····2pcs.

			Stroke Speed	troke Speed (c.p.m.) Air Consumption (m²/min)	Stroke (mm)	Hose Coupling	Overall Length (mm)	Weight (g)	Accessories		
Model No.	Cutting Capacity		(c.p.m.)						Plug	L-wrench	EDP No.
GT-AS10	Metal sheet…4mm	0.6	5,000	0.28	10	Rc 1/4	195.5	870	BPB-2	Н3	336131
GT-AS100	Metal sheet…1.6mm	0.6	10,000	0.34	10	Rc 1/4	170	570	BPB-2	H2,H4	310640

Cutting capacity: GT-AS10: When used with a No.ABS-32H blade GT-AS100: When used with a No.ASB-32 blade Overall Length and Weight: Accessories not included.

Air Saw Blades (For GT-AS10/AS100)



Model No.	Specifications	Use	Quantity	EDP No.
ASB-32	For steel Cobalt mix, standard blade, 32 teeth	Cutting steel	10	350054
ASB-32H	For steel Cobalt mix, super thick blade, 32 teeth	Cutting plain and stainless steel sheet	10	350052
ASB-24H	For steel Cobalt mix, super thick blade, 24 teeth	Cutting aluminum, soft steel and resin	10	350053
ASC-25-5	Scraper 25 mm wide blade	Scraping, peeling, etc.	1	350143

STATIC SOLUTIONS



Noise reducer

% Scraper sold separately

↓ See One point

Model No.	Working Air	Stroke Speed (c.p.m.)	Air Consumption (m²/min)	Stroke (mm)	Hose Coupling	Overall Length	Weight	Accessories		500.11
	Pressure (MPa)					(mm) (g)	(g)	Plug	L-wrench	EDP No.
GT-ASC5	0.6	7,000	0.28	5	Rc 1/4	195.5	810	BPB-2	H3	336132

Scraper (For GT-ASC5)

No. ASC-25-8



No. ASC-50-8




Model No.	Blade Width (mm)	Axis Dia. φ (mm)	Use	EDP No.	
ASC-25-8	25	8	for IC chip	350141	
ASC-50-8	C-50-8 50 8		for IC chip, wall	350142	

One point

Ideal for recycling of automotive and PC



Use to detatch IC chips from circuit boards when recycling PCs, faxes, copiers.



1/4**-**28UNF

available snake drills.

No. GT-CD60-34L

ELECTRIC TOOLS

Drill Hole bhmm Compact and lightweight. Equipped with adjust-valve and silencer, which offer comfort to operators



No. GT-CD60-34

available snake drills.

Air Corner Drill

Rear exhaust

Drill Hole ϕ 8mm Compact, lightweight, and noise reducer equipped, for comfort to the workplace.

1/4-28UNF



Drill Hole ϕ 10mm Compact, lightweight, and noise reducer equipped, for comfort to the workplace.



0.0 - 0.1 -	Steel Plate Drilling	No Load Speed	Air Consumption	6 "	Air Hose Inner	Overall Length	Weight	Chuck Size	Accessories		EDD NI
Model No.	Capacity φ (mm)	(rpm)	(m/min)	Hose Coupling	Dia. (mm)	(mm)	(g)	(mm)	Plug		EDP No.
GT-D60-30	6	3,000	0.52	Rc 1/4	6.35	188	880	6.0	BPB-2	Chuck handle	310603
GT-D60-45	6	4,500	0.56	Rc 1/4	6.35	188	890	6.0	BPB-2	Chuck handle	310611
GT-CD60-34	6	3,400	0.42	Rc 1/4	6.35	250	820	6.0	BPB-2	Lock Offset handle, wrench	336141
GT-CD60-34L	6	3,400	0.42	Rc 1/4	6.35	251	840	6.0	BPB-2	Lock Offset handle, wrench	336142
GT-D80-20	8	2,000	0.35	Rc 1/4	6.35	165	940	8.0	BPB-2	Chuck handle	310604
GT-D80-20K	8	2,000	0.35	Rc 1/4	6.35	171	960	8.0	BPB-2	_	310605
GT-D100-15	10	1,500	0.54	Rc 1/4	6.35	189	1,280	10.0	BPB-2	Chuck handle	310606
GT-D100-15K	10	1,500	0.54	Rc 1/4	6.35	195	1,300	10.0	BPB-2	_	310607

·Working air pressure: 0.6MPa ·Overall length and Weight: Accessories not included.