

No. 220USB-1E



**Screwdrivers** make progress.

Replacement bits also make progress.

hexagon

bolster



 $\oplus$ 1× $\phi$ 4.5×100

 $\oplus 2 \times \phi 5 \times 100$ 

 $\oplus 2 \times \phi 5 \times 150$ 

Replacement Bits with Spanner Hexagon Bolster

160×35×8

10

10

Card Size(mm) Inner Ctn. Outer Ctn. EDP No.

Be sure to fully read the instruction manual of the product.
 Be careful of the short-circuit accident or electricity shock

Overloaded use may cause damages in screws or injuries.

200

10 200

485803

485804

485805

Slim and tube-covered

shank type.

USB161100

USB162100

USB162150

USB163100

USB166100

Model No.

**USB163100S8** ⊕3×φ7×100

8mm spanner bolster

Line-up: Replacement Bits for the 220USB-1E

POINT 01	S
	h

screw.

Can tighten or loosen with a spanner (also adjustable spanner). Good for applications requiring a high torque work.



A tube covers the bit shank for prevention of short-circuit accidents or scratch damages on your product. \*Not insulated. Be careful because the hexagon bolster can conduct electricity.



Good for loosening screws stuck because of rust, and for high torque screw tightening. Also good for switchboard disassembly and transfer.

## **VESSEL Co., Inc.**

Spanner hexagon bolster

facilitates to remove a stuck

17-25, Fukae-Kita 2-chome, Higashinari-ku, Osaka 537-0001 JAPAN Tel:+ 81 (0) 6 6976 7778 Fax:+ 81 (0) 6 6972 9441 E-mail:export@vessel.co.jp URL: www.vessel.co.jp/english/

		•Keep away this product from children.	
Distribu	ted by		
			20081800.00

•Specifications, dimensions, and others, may be subject to change without prior notice.

















160g

# Electric

**Electric-powered quick tightening!!** 

# Manual

Outstanding
Ephiciency

Electric or facility work Switchboard assembly

**Equipment maintenance** Automotive or motorcycle maintenance

**Manual final tightening!!** 

**Light-weight** 

Carry the 220USB-1E in your waist bag.

Approx.550g

Pen type

electric screwdriver

VESSEL's Ball Grip Screwdrivers, providing the outstanding work efficiency, have made great progress. An electric-powered new solution with a lithium-ion battery and a motor.

#### Switch

Sliding switch enables to change the rotation direction, either clockwise or counterclockwise, with a light force.





USB Recharge **USB** Recharge Easy to recharge via USB terminal.

43.6<sub>v</sub> / 800mAh **Battery Charger Lamp** Li-ion Battery





\* For circuit-board protection, the lamp of the 220USB flashes red and the screwdriver stops operation, when a load such as 2N·m or over is given during electric-powered use. If the charge level of the battery is less than 15%, the battery charge lamp will flash red during operation

#### High Brightness **LED**

**LED light** Illuminates in a dark working place.

#### **Sleeve Chuck**

Both double-end and single-end bit can be used.







High speed revolutions improves work efficiency!

No-load revolutions: 280min-1

Can be used with a screw upto M6. Torque range : Electric 2N·m or less, Manual 10N·m or less

### Electric-powered hand tool newly available. **VESSEL Electric-powered Ball Grip Screwdriver**



#### How to use

1) Slide the switch forward to rotate to the right (clockwise: tighten), and slide backward to rotate to the left (counterclockwise;

loosen). 2) Position yourself and hold the grip firmly.



- 3) Operate the switch to start tightening. (Tentative tightening)
- Release the switch at the moment when the screw sits. Then, hold again the grip to tighten slowly by hand (final tightening) until you feel that the gears were locked.



<Note> Excessive load will lead to failure. Do not use this product for a screw that needs to be loosened with two hands. The small gears are built in so that the screwdriver fits into the waist sack.

### No. 220USB-1E **USB** Rechargeable Screwdriver

 Accessories: USB cable, Bit (1pc each)

USB Charging Cable (1m)

		Outer Carton, 5 sets
Model No.	Accessories	EDP No.
220USB-1E	Bit:⊕2 (100mm) USB Charging Cable (1m)	148513

Package size: W105 x H250 x D75(mm)

	Main Body
Name	USB Rechargeable Screwdriver
Model	220USB-1E
Battery capacity	Li-Ion 3.6V 800mAh
No-load revolutions (max)	280min <sup>-1</sup>
Torque (max)	2N·m(Electric)
Rated torque (manual turning)	10N·m
Sleeve	Hex 6.35mm, Aluminum sleeve chuck
Applicable bit	Hex 6.35mm, Single-end or Double-end bi
Charging time	Approx. 60min.
Number of charges *	Approx. 500times
Continuous use time	Approx. 40min. (no-load)
Number of screw tightening	Approx. 200times (M4x20mm)
Charging method	Micro USB-typeB, USB charging
Input (max)	5V 1A
Weight	160g (Accessories not included)
Operation/charging environment	-10℃~45℃ / 0℃~40℃

Battery Charger	
Input	100~240VAC, 50/60Hz
Output	5V 1A

\*Actual battery lifetime may vary, depending on the use conditions and \*Battery cannot be replaced.