


*New***Cable Stripper****Easy to strip the wire sheath simply by turning the stripper around the cable.**

Light-weight and compact portable model.

**EDP No.141224  
3700KS**Applicable  
Wire O/D**Φ4~16mm****EDP No.141225  
3700KM**Applicable  
Wire O/D**Φ8~28mm****Easy-handling non-slip pad on retaining hardware.****Easy-to-grasp non-slip ergonomic grip.****Enables to adjust the cutting depth with a dial on the bottom.****Applications**

Cabtyre cable, Removal of sheath from a cord, communication cable, and so on.

## No.3700KS Cable Stripper



●Accessory: Replacement blade (1piece)(stored inside)



Model No.	Overall Length (mm)	Weight (g)	Applicable (Stripping range)	Inner Ctn. (Piece)	EDP No.
<b>3700KS</b>	131	79	Sheath dia.4~16mm	10	141224

Cardboard size : 185×75×32mm

## No.3700KM Cable Stripper




●Accessory: Replacement blade (1piece)(stored inside)




Model No.	Overall Length (mm)	Weight (g)	Applicable (Stripping range)	Inner Ctn. (Piece)	EDP No.
<b>3700KM</b>	133	80	Sheath dia.8~28mm	10	141225

Cardboard size : 185×75×32mm

### How to use



① Dial



Push

②



2-3 turns

③



④ Pull

1) Adjust the blade cutting depth by turning the dial on the bottom.

\*Improper adjustment of the depth may cause damage on the wires or on the blade.


2) Hold a cable with the retaining hardware and sink the blade into the cable.

3) Hold the cable and push up the stripper from the underside to cut the sheath, like the illustration above.

4) Move laterally the stripper while holding the cable to strip the sheath.

\*The edge of the retaining hardware is convenient to peel off the solid sheath by insert it into the cutting trace.


### How to replace blades



① Screws (2 places)



②



New blade

Used blade



Dial

1) Unfasten 2 screws on the body.

2) Lift slightly the upper cover and slide it toward the dial to open.

3) Replace the used blade with the new one. Mount it on the same place.

4) Re-assemble in the reverse order of disassembly. Check the rotation of the dial.

### Best Seller! Wire Stripper Series

## No. 3500E-1/-2 Wire Stripper



3500E-1 3500E-2

- Lightweight (100g), compact handy type.
- Diamond finely polished blade for precision stripping.
- AWG-mm-mm<sup>2</sup> conversion table on the grip.



Model No.	Overall Length (mm)	Weight (g)	Handle	Inner Ctn. (Piece)	Outer Ctn. (Piece)	EDP No.		
<b>3500E-1</b>	155	100	赤	5	30	014108		
<b>3500E-2</b>	155	100	黄	5	30	014115		
<b>3500E-1</b>	AWG	12	14	16	18	20	22	24
	Solid wire (mm)	2.0	1.6	1.3	1.0	0.8	0.65	0.5
<b>3500E-2</b>	AWG	18	20	22	24	26	28	30
	Solid wire (mm)	1.0	0.8	0.65	0.5	0.4	0.3	0.25
	Standard wire (mm)	0.8	0.5	0.3	0.2	0.13	0.08	0.05

Cardboard size : 220×75×13mm

### CAUTION

- NEVER USE FOR HOT-LINE JOB. RISQUE OF ELECTRICAL SHOCK. ●This product is not insulated.
- Don't finger the blade to avoid injury. ●Use this product after understanding the suitable applications, sizes, and how to use.
- Keep this product away from children.

## VESSEL Co., Inc.

17-25, Fukae-Kita 2-chome, Higashinari-ku, Osaka 537-0001 JAPAN  
Tel : +81(0)6 6976 7778 Fax : +81(0)6 6972 9441

### VESSEL EUROPE

6, avenue du 1er Mai, ZAE Les Glaises, 91120 Palaiseau FRANCE  
Tel : +33(0)1 69 19 17 42 Fax : +33(0)1 69 19 42 20

E-mail : export@vessel.co.jp URL : http://www.vessel.co.jp/english/

### Distributed by

17062000.00